



Lem<sup>o</sup>n fresh Fragrance

# WEATHER@Guard

100% Acrylic Exterior Wall Finish

- Fungus Resistant
- All Weather Application
- Dirt Resistant
- Lead & Mercury Free
- Self Cleaning, Excellent Durability
- Breathable Film
- Excellent Coverage & Adhesion

*Extra*



# WEATHER@Guard



100% Acrylic Exterior Wall Finish  
Product Standard : W/WG/9000 Series

*Extra*



Pebblewalk **WG 9548**



Porcelain **WG 9703**



Pebbles **WG 9345**



McClendon **WG 9926**



Windmill White **WG 9719**



Purple Lint **WG 9083**



Orion **WG 9273**



Fog Grey **WG 9988**



Zambezi Rock **WG 9566**



Purple Grey **WG 9160**



Cement **WG 9507**



Desert Isle **WG 9587**



Tendrils **WG 9569**



Tungsten **WG 9412**



Burmese Beige **WG 9729**



Field Stone **WG 9129**



Tanzania **WG 9598**



Mercury **WG 9235**



Monterrey **WG 9662**



Rocky Nook **WG 9401**



Breezy Palms **WG 9583**



Gunsmoke Grey **WG 9307**



Neutral **WG 9500**



Tobacco Brown **WG 9522**



Kenyan Leaves **WG 9599**



Ominous **WG 9989**



Rugged **WG 9582**



Coffee House **WG 9517**



Sanctuary **\*\*WG 9584**



Dawn Grey **WG 9747**



Woodgrove **WG 9574**



Terra Cotta **WG 9407**

▲ Obsolete colour, available while stock last.

\*\* Premium Colours

● Ready Product

Also available in WHITE WG 9004 & BLACK WG 9000

# Lemon fresh Fragrance

- Fungus Resistant
- All Weather Application
- Dirt Resistant
- Lead & Mercury Free
- Self Cleaning, Excellent Durability
- Breathable Film
- Excellent Coverage & Adhesion



Morning Dew **WG 9202**



Sunflower White **WG 9451**



Rose Fever **WG 9117**



Glacier Blue **WG 9190**



Cream **WG 9140**



Banana **WG 9138**



Persimmon White **WG 9452**



Ocean White **WG 9610**




Vanilla **WG 9704**



Citron Ice **WG 9147**



▲ Sunset **WG 9254**



Cascade **WG 9269**



▲ Abbeystone **WG 9705**



French Linen **WG 9535**



Trendy **WG 9272**



Cool Comfort **WG 9281**



Sandstone Mix **WG 9653**



● Yellow Boy **\*\*WG 9898**



e.purple **WG 9003**



Lettuce **WG 9149**



Vistasik Brown **WG 9655**



● Pure Gold **\*\*WG 9453**



Prophetic Purple **\*\*WG 9183**



Apple Pie **\*\*WG 9977**



Mocha Woods **WG 9658**



● Orange Farm **WG 9604**



Exotic Bloom **\*\*WG 9036**



▲ Blue Eye's **WG 9993**



Native Soil **\*\*WG 9124**



● Orange lantern **\*\*WG 9105**



● e.red **\*\*WG 9002**



Wira Blue **\*\*WG 9221**



## DESCRIPTION

**SANcora® WEATHER@Guard Extra** is a premium quality, 100% full acrylic-based emulsion paint. It is specially formulated for tropical climates with excellent weathering properties. It is also fungus and algae resistant. **SANcora® WEATHER@Guard Extra** 100% acrylic-based exterior wall finish has excellent alkali resistance, adhesion and durability. It is formulated to provide at least 6 years protection against fungus and algae growth with correct application.

<b>USAGE</b>	For decorative and protection of previously-painted or new exterior walls for a long-lasting aesthetic finish.
<b>TECHNICAL DATA</b>	<p>Texture : Smooth Matt Finish</p> <p>Theoretical Coverage : Approx. 13 - 15m<sup>2</sup> / litre (Depending on surface evenness)</p> <p>Drying Time : Single coat at standard thickness (28°C, 50% RH)</p> <p>Touch Dry ≤ 45 minutes</p> <p>Hard Dry ≤ 2 hours</p> <p>Recoating Time : 2 hours</p> <p>Thinner / Cleaner : Water</p>
<b>SURFACE PREPARATION</b>	<p><b>General / New</b> : Surfaces must be sound, clean, dry and free from all defective or poorly adhering materials, dirt, grease or wax. To have better finish, rub down surface using suitable abrasive and dust off. For the best result, seal with one coat of appropriate <b>SANcora® BLOCK@Guard</b>.</p> <p><b>Previously Painted</b> : Remove all loose, defective and unstable paint film or powdery residue by brushing thoroughly and scraping. Repair minor defects and cracks with suitable filler.</p>
<b>SHELF LIFE</b>	2 years at ambient temperature in unopened containers.

## PAINT GUIDE

Surface Condition	Primer - To Paint 1 Coat	Finishing - To Paint 2 Coats
Powdery Surfaces / Alkaline / New Surfaces	<b>SANcora® BLOCK@Guard</b> Hi-Performance Wall Sealer	<b>SANcora® WEATHER@Guard</b> Extra
Sound Surfaces / Previously Painted Surfaces	<b>SANcora® BLOCK@Guard</b> Alkali Resistant Wall Sealer	<b>SANcora® WEATHER@Guard</b> Extra

## SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

- When applying paint, it is advisable to wear eye protection and suitable gloves.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
- Remove splashes of paint from skin by using soap or water.
- Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
- Ensure good ventilation during application and drying.
- Paint must always be stored in upright position and a cool dry place.
- Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
- Refer to Material Safety Data Sheet for complete product safety information.

## PENERANGAN

**SANcora® WEATHER@Guard** Extra merupakan cat berkualiti premium dengan 100% emulsi akrilik. Ianya diformulasi khas untuk iklim tropika dengan daya tahan cuaca yang unggul. Ianya juga mempunyai ketahanan terhadap kulat dan alga. **SANcora® WEATHER@Guard** Extra 100% cat akrilik dinding luaran mempunyai rintangan alkali, adhesi dan daya tahan yang unggul. Ianya diformulasi untuk mempunyai perlindungan terhadap pertumbuhan kulat dan alga selama 6 tahun jika diaplikasi dengan cara yang betul.

<b>PENGGUNAAN</b>	Untuk penghiasan dan perlindungan pada dinding baru atau dinding pernah dicat dengan kemas estetik yang lebih tahan lasak.
<b>DATA TEKNIKAL</b>	<p>Tekstur : Halus dan Matt</p> <p>Liputan Teori : Anggaran. 13 - 15m<sup>2</sup> / liter (Bergantung pada kelicinan permukaan)</p> <p>Tempoh Kering : Satu lapisan dengan ketebalan standard (28°C, 50% RH)</p> <p>Kering disentuh ≤ 45 minit</p> <p>Kering sempurna ≤ 2 jam</p> <p>Tempoh Lapisan Semula : 2 jam</p> <p>Pencair / Pencuci : Air</p>
<b>PENYEDIAAN PERMUKAAN</b>	<p><b>Umum / Baru</b> : Permukaan mesti licin, bersih, kering dan bebas daripada sebarang kekotoran, minyak atau wax. Untuk pengecatan lebih baik, gosok permukaan dengan kertas kasar yang sesuai. Untuk kemas yang paling baik, sapukan permukaan dengan satu lapisan <b>SANcora® BLOCK@Guard</b>.</p> <p><b>Pernah Dicap</b> : Tanggalkan semua cat yang mengelupas, baki berserbuk dan bendasing. Baiki kecacatan permukaan dengan Filler yang sesuai.</p>
<b>JANGKA HAYAT</b>	2 tahun pada suhu bilik dalam bekas tertutup.

## PANDUAN MENGECAT

Keadaan Permukaan	Cat Asas - Cat 1 Lapisan	Kemas Akhir - Cat 2 lapisan
Permukaan Bersebuk / Alkali / Permukaan Baru	<b>SANcora® BLOCK@Guard</b> Hi-Performance Wall Sealer	<b>SANcora® WEATHER@Guard</b> Extra
Permukaan Baik / Permukaan pernah dicat	<b>SANcora® BLOCK@Guard</b> Alkali Resistant Wall Sealer	<b>SANcora® WEATHER@Guard</b> Extra

## INFOMASI KESELAMATAN, KESIHATAN DAN PERSEKITARAN

- Semasa mengecat adalah disyorkan memakai perlindungan mata dan sarung tangan yang sesuai.
- Jika mata terkena cat, cuci dengan air yang banyak dan segera berjumpa doctor.
- Bersihkan sebarang cat yang terkena pada kulit dengan sabun dan air.
- Pastikan bekas cat ditutup rapat dan jauhkan daripada makanan, minuman dan kanak-kanak.
- Pastikan ada pengudaraan yang baik semasa pengecatan dan pengeringan.
- Bekas cat mesti disimpan dalam kedudukan tegak dan tempat sejuk dan kering.
- Lupuskan semua sisa cat menurut Peraturan Kualiti Alam Sekitar.
- Rujuk kepada lembaran MSDS untuk maklumat yang lebih terperinci.

### Paint Manufacturer

**SANCORA PAINTS INDUSTRIES SDN BHD** (19733-T)

Lot 8206, Kawasan Perusahaan Kamunting, 34600 Kamunting, Perak, Malaysia.

Tel +605-891 8777 (8 lines) Fax +605-891 2277 Email info@sancora.com Website www.sancora.com

 www.facebook.com/sancorapaint

### Paint Distributor

**SANCORA PAINTS MARKETING SDN BHD** (716878-P)

### THE MARK OF QUALITY

Quality Management Systems Certification By :-

