



WEATHER *Max*

ACRYLIC EXTERIOR PAINT

- Fungus Resistant
- All Weather Application
- Dirt Resistant
- Excellent Coverage & Adhesion
- Lead & Mercury Free



Golden Bull Award
2003, 2004 & 2007
Malaysia 100 Outstanding SMEs



WEATHER *Max*

ACRYLIC EXTERIOR PAINT



Banana **WM 22138**



Cheese House **WM 26602**



Pebbles Classic **WM 26345**



Ocean White **WM 21610**



Buttermilk **WM 22140**



Summer Daisy **WM 26454**



Mandarin Fields **WM 26565**



Sunflower White **WM 26451**



Orion **WM 26273**



Creme Brulee **WM 27141**



French Linen **WM 26535**



Persimmon White **WM 26452**




Calypso **WM 24255**




Apple **WM 26603**



Orange Farm **WM 26604**



Sand Tune **WM 24371**



Tangerine **WM 24254**



Orange Lantern **WM 27105**



Pure Gold **WM 26453**



Galaxy **WM 22334**



Cherry Blossom **WM 24258**



Purple Lint **WM 21083**



McClendon **WM 22926**



Sandstone **WM 22653**



Apricot **WM 22135**



Maldivian Cloud **WM 21684**



Fog Grey **WM 20988**



Vistasik Brown **WM 22655**



Choco Malt **WM 27123**



Tungsten **WM 20412**



Burmese Beige **WM 26729**



Monterrey **WM 22662**



Carmel **WM 26533**



Mercury **WM 20235**



Zambezi Rocks **WM 26566**



Rocky Mountain **WM 22670**



Mocha Woods **WM 22658**



Whetstone **WM 20987**



Waterfall Hills **WM 23416**



South Alps **WM 24565**



Terra Cotta **WM 22199**



Ominous **WM 20989**



Tanzania **WM 23598**



Boutique **WM 22136**



Wira Blue **WM 21221**



Dawn Grey **WM 20747**



Kenyan Leaves **WM 23599**

SANcora® WEATHER-Max is a good quality, acrylic copolymer exterior paint. It is specially formulated for tropical climates with good weathering properties. It is also fungus and algae resistant. **SANcora® WEATHER-Max** acrylic exterior paint has excellent alkali resistance, adhesion and durability. It is formulated to provide at least 3 years protection against fungus and algae growth with correct application.

USAGE

For decorative and protection of previously-painted or new exterior walls for a long-lasting aesthetic finish.

TECHNICAL DATA

Texture	: Smooth Matt Finish	Recoating Time	: 2 hours
Theoretical Coverage	: Approx. 13 - 15m ² / litre (Depending on surface evenness)	Thinner/Cleaner	: Water
Drying Time	: Single coat at standard thickness (28°C, 50% RH)		
	• Touch Dry ≤ 45 minutes		
	• Hard Dry ≤ 2 hours		

SURFACE PREPARATION

General / New

Surfaces must be sound, clean, dry and free from all defective or poorly adhering materials, dirt, grease or wax. To have better finish, rub down surface using suitable abrasive and dust off. For the best result, seal with one coat of appropriate **SANcora® BLOCK@Guard**.

Previously Painted

Remove all loose, defective and unstable paint film or powdery residue by brushing thoroughly and scraping. Repair minor defects and cracks with suitable filler.

SHELF LIFE

2 years at ambient temperature in unopened containers.

PAINT GUIDE

Surface Condition	Primer - To Paint 1 Coat	Finishing - To Paint 2 Coats
Powdery Surfaces / Alkaline / New Surfaces	SANcora® BLOCK@Guard Hi-Performance Wall Sealer	SANcora® WEATHER-Max
Sound Surfaces / Previously Painted Surfaces	SANcora® BLOCK@Guard Alkali Resistant Wall Sealer	SANcora® WEATHER-Max

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

When applying paint, it is advisable to wear eye protection and suitable gloves.
 In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
 Remove splashes of paint from skin by using soap or water.
 Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
 Ensure good ventilation during application and drying.
 Paint must always be stored in upright position and a cool place.
 Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
 Refer to Material Safety Data Sheet for complete product safety information.

SANcora® WEATHER-Max merupakan cat luaran kopolimer yang berkualiti baik. Ianya diformulasi khas untuk iklim tropika yang mempunyai daya ketahanan cuaca. Ianya juga mempunyai ketahanan terhadap kulat dan alga. **SANcora® WEATHER-Max** cat akrilik dinding luaran mempunyai rintangan alkali, adhesi dan daya tahan yang baik. Ianya diformulasi untuk mempunyai perlindungan terhadap pertumbuhan kulat dan alga selama 3 tahun jika diaplikasi dengan cara yang betul.

PENGGUNAAN

Untuk penghiasan dan perlindungan pada dinding baru atau dinding pernah dicat dengan kemasan estetik yang lebih tahan lasak.

DATA TEKNIKAL

Tekstur	: Halus dan Matt	Tempoh Lapisan semula	: 2 jam
Liputan Teori	: Anggaran 13 - 15m ² / liter (Bergantung pada kelicinan permukaan)	Pencair / Pencuci	: Air
Tempoh Kering	: Satu lapisan dengan ketebalan standard (28°C, 50% RH)		
	• Kering disentuh ≤ 45 minit		
	• Kering sempurna ≤ 2 jam		

PENYEDIAAN PERMUKAAN

Umum / Baru

Permukaan mesti licin, bersih, kering dan bebas daripada sebarang kekotoran, minyak atau wax. Untuk pengecatan lebih baik, gosok permukaan dengan kertas kasar yang sesuai. Untuk kemasan yang paling baik, sapukan permukaan dengan satu lapisan **SANcora® BLOCK@Guard**.

Pernah Dicatkan

Tanggalkan semua cat yang mengelupas, baki berserbuk dan bendasing. Baik kecacatan permukaan dengan Filler yang sesuai.

JANGKA HAYAT

2 tahun pada suhu ambien dalam bekas tertutup.

PANDUAN MENGECAT

Keadaan Permukaan	Cat Asas – Cat 1 lapisan	Kemasan Akhir – Cat 2 lapisan
Permukaan Berserbuk / Alkali / Permukaan Baru	SANcora® BLOCK@Guard Hi-Performance Wall Sealer	SANcora® WEATHER-Max
Permukaan Baik / Permukaan pernah dicat	SANcora® BLOCK@Guard Alkali Resistant Wall Sealer	SANcora® WEATHER-Max

INFOMASI KESELAMATAN, KESIHATAN DAN PERSEKITARAN

Semasa mengecat adalah disyorkan memakai perlindungan mata dan sarung tangan yang sesuai.
 Jika mata terkena cat, cuci dengan air yang banyak dan segera berjumpa doctor.
 Bersihkan sebarang cat yang terkena pada kulit dengan sabun dan air.
 Pastikan bekas cat ditutup rapat dan jauhkan daripada makanan, minuman dan kanak-kanak.
 Pastikan ada ventilasi yang baik semasa pengecatan dan pengeringan.
 Bekas cat mesti disimpan dalam keadaan tegak dan kawasan yang sejuk.
 Buangkan semua sisa cat menurut Peraturan Kualiti Alam Sekitar.
 Rujuk kepada lembaran MSDS untuk maklumat yang lebih terperinci.

Paint Manufacturer

SANCORA PAINTS INDUSTRIES SDN BHD (19733-T)

Lot 8206, Kawasan Perusahaan Kamunting, 34600 Kamunting, Perak, Malaysia.

Tel +605-891 8777 (7 lines) Fax +605-891 2277 Email info@sancora.com Website www.sancora.com

www.facebook.com/sancorapaint

Paint Distributor

SANCORA PAINTS MARKETING SDN BHD (716878-P)

THE MARK OF QUALITY

Quality Management Systems Certification By :-



Intertek



Age No : Q117798



074

