

TECHNICAL DATA SHEET

Elasta@Guard

~ Floor Coating (Anti-Slip) ~

Document No: TB-IC-05

SANcora® ELASTA@Guard Floor Coating is based on Vinyl-Acrylic Copolymer that gives a tough, durable and flexible paint film. It is formulated with fungus and algae resistant and able to withstand harsh environment.

| | | |
|----------------------------|--|--|
| Usage | Suitable for decorative and protective used on all concrete surfaces, flooring, fair faced bricks, asbestos roofing, cement board and etc. | |
| Pack Size | 5 litres | |
| Composition | Pigment | : Organic & Inorganic |
| | Binder | : Vinyl-Acrylic Copolymer |
| | Vehicle/Solvent | : Water |
| Technical Data | Texture | : Smooth Mid Sheen Finish |
| | Colour | : Refer to Industrial Coating Colourcard |
| | Theoretical Coverage | : Approx. 13 - 15m ² / litre (Depending on surface evenness) |
| | Drying Time | Single coat at standard thickness (28°C, 50% RH) |
| | | : Touch Dry ≤ 45 minutes |
| | | : Hard Dry ≤ 2 hours |
| | Recoating Time | : 2 hours |
| | Thinner/Cleaner | : Water |
| Application | Brush/Roller | : For normal use, thinning is not necessary. To assist application, can be thinned 5 - 10% by volume with water. |
| | Conventional Air Spray | : Thin 10 - 20% by volume with water and adjust to requirement. |
| | Airless Spray | : Thinning is not required. To assist application, can be thinned 10 - 20% by volume with water. |
| Surface Preparation | General / New | : Surfaces must be sound, clean, dry and free from all defective or poorly adhering materials, dirt, grease or wax. To have better finish, rub down surface using suitable abrasive and dust off. Remove all loose, defective and unstable paint film or powdery residue by brushing thoroughly and scraping. High pressured water jet is highly recommended. Treat area affected by mould, lichens, algae and moss with appropriate fungi wash. Repair minor defects and cracks with suitable filler. |
| | Previously Painted | : |
| Shelf Life | 2 years at ambient temperature in unopened containers. | |

Paint Guide

| Surface Condition | Finishing - To Paint 2 Coats |
|---|------------------------------|
| Powdery Surfaces / Alkaline / New Surfaces | SANcora® ELASTA@Guard |
| Sound Surfaces / Alkaline / Previously Painted surfaces | SANcora® ELASTA@Guard |

Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.
 In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
 Remove splashes of paint from skin by using soap or water.
 Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
 Ensure good ventilation during application and drying.
 Paint must always be stored in upright position and a cool place.
 Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
 Refer to Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

SANCORA PAINTS INDUSTRIES SDN BHD (19733-T)

Lot 8206, Kawasan Perusahaan Kamunting, 34600 Kamunting, Perak, Malaysia

Tel: +605-891 8777 (8 Lines) Fax: +605-891 2277 Email: info@sancora.com

Website: www.sancora.com Facebook: www.facebook.com/SancoraPaint