Revision Date: 24/06/2016

TECHNICAL DATA SHEET

I-EMULSION

~ Interior & Exterior Emulsion Paint ~

Document No: TB-IP-06

I- Emulsion is a good quality value for money, acrylic copolymer interior emulsion paint. It is generally formulated to protect and decorate normal interior walls and ceiling surfaces.

Usage

For decorative and protection of previously-painted or new interior walls and ceiling.

Pack Size

1 litre, 5 litres and 15 litres.

Composition

Pigment	:	Organic and Inorganic
Binder	:	Acrylic Copolymer Emulsion
Vehicle	:	Water

Technical Data

Texture	:	Smooth Matt Finish
Colour	:	Refer to Inspiration colours collection colourcard
Theoretical Coverage	:	Approx. 11 - 13m^2 / litre (Depending on surface evenness)
Drying Time	:	Single coat at standard thickness (28ºC, 50% RH) Touch Dry ≤ 45 minutes Hard Dry ≤ 2 hours
Recoating Time	:	2 hours
Thinner/Cleaner	:	Water

Application

Brush/Roller	:	For normal use, thinning is not necessary. To assist application, can be thinned up to 5% by volume with water.
Conventional Air Spray	:	Thin 5 - 15% by volume with water and adjust to requirement.
Airless Spray	:	Thinning is not required. To assist application, can be thinned 5 - 15% by volume with water.

Surface Preparation

General / New	:	Surfaces must be sound, clean, dry and free from all defective or poorly adhering materials, dirt, grease or wax. To have better finish, rub down surface using suitable abrasive and dust off. For the best result, seal with one coat of appropriate ***SANcora***® BLOCK@Guard.
Previously Painted	:	Remove all loose, defective and unstable paint film or powdery residue by brushing thoroughly and scraping. Repair minor defects and cracks with suitable filler.

Shelf Life

2 years at ambient temperature in unopened containers.

Paint Guide

Surface Condition	Primer - To Paint 1 Coat	Finishing - To Paint 2 Coats
Powdery Surfaces / Alkaline / New Surfaces	***SANcora***® BLOCK@Guard Hi-Performance Wall Sealer	***I-Emulsion***
Sound Surfaces / Previously Painted Surfaces	***SANcora***® BLOCK@Guard Alkali Resistant Wall Sealer	***I-Emulsion***

Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.
In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
Remove splashes of paint from skin by using soap or water.
Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
Ensure good ventilation during application and drying.
Paint must always be stored in upright position and a cool place.
Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
Refer to Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

SANCORA PAINTS INDUSTRIES SDN BHD **(19733-T)**
Lot 8206, Kawasan Perusahaan Kamunting, 34600 Kamunting, Perak. Malaysia
Tel: +605-891 8777 (8 Lines) Fax: +605-891 2277 Email: info@sancora.com
Website: www.sancora.com Facebook: www.facebook.com/SancoraPaint