

TECHNICAL DATA SHEET

STONE@Guard

~ Acrylic Interior & Exterior Stone Dressing ~

Document No: TB-OP-01

SANcora® STONE@Guard is formulated with acrylic resin. It gives high gloss retention, excellent brushability and abrasion resistance. It is also excellent in acid and alkali resistance and provides a coat of high sheen smooth finish. Suitable for structures with dull and matt cobblestone or tiles surfaces.

Usage	Recommended used for cobblestone pave way or car porch. It is also suitable on matt tiles surface structures.	
Pack Size	1 litre, 5 litres and 18 litres.	
Composition	Binder	: Acrylic Resin
	Vehicle/Solvent	: Aromatic Hydrocarbon
Technical Data	Texture	: High Sheen Smooth Finish
	Colour	: Clear
	Theoretical Coverage	: Approx. 15- 17m ² / litre (Depending on surface evenness)
	Drying Time	Single coat at standard thickness (28°C, 50% RH)
		: Touch Dry ≤ 3 hours
		: Hard Dry ≤ 8 hours
	Recoating Time	: 6 hours
	Thinner/Cleaner	: Mineral Spirit
Application	Brush/Roller	: Ready for use
	Conventional Air Spray	: Ready for use
	Airless Spray	: Ready for use
Surface Preparation	Cobblestone or tiles	: Surfaces must be sound, clean, dry and free from all defective or poorly adhering materials, dirt, sands, grease or wax.
Shelf Life	2 years at ambient temperature in unopened containers.	

Paint Guide

Surface Condition	Finishing - To Paint 2 Coats
New cobblestone/ tiles	<i>SANcora</i> ® STONE@Guard
Previously Painted cobblestone / tiles	<i>SANcora</i> ® STONE@Guard

Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.
 In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
 Remove splashes of paint from skin by using soap or water.
 Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
 Ensure good ventilation during application and drying.
 Paint must always be stored in upright position and a cool place.
 Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
 Refer to Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

SANCORA PAINTS INDUSTRIES SDN BHD (19733-T)

Lot 8206, Kawasan Perusahaan Kamunting, 34600 Kamunting, Perak, Malaysia

Tel: +605-891 8777 (8 Lines) Fax: +605-891 2277 Email: info@sancora.com

Website: www.sancora.com Facebook: www.facebook.com/SancoraPaint