

TECHNICAL DATA SHEET

GLOSS@Guard

~ Exterior Hi-Gloss Paint ~

Document No: TB-WM-01

SANcora® GLOSS@Guard is a premium solvent-based high gloss paint, suitable for use on all types of wood and metal surfaces. It is a fungus-resistant high gloss architectural paint that is easy to apply and forms a smooth mirror-like tough paint film with excellent gloss and durability.

Usage	For decorative and protection of all types of interior and exterior wood and metal surfaces. It is also ideal for use as a marine enamel for topsides, deckhouse and engine rooms.	
Pack Size	1 litre, 5 litres and 18 litres.	
Composition	Pigment	: Organic & Inorganic
	Binder	: Modified Alkyd
	Vehicle/Solvent	: White Spirit
Technical Data	Texture	: High Gloss Smooth Finish
	Colour	: Refer to GLOSS@Guard Colourcard
	Theoretical Coverage	: Approx. 14- 16m ² / litre (Depending on surface evenness)
	Drying Time	Single coat at standard thickness (28°C, 50% RH)
		: Touch Dry ≤ 4 hours
		: Hard Dry ≤ 18 hours
	Recoating Time	: 10 hours
	Thinner/Cleaner	: White Spirit or Mineral Turpentine
Application	Brush/Roller	: For normal use, thinning is not necessary. If required, add up to 10% by volume with White Spirit.
	Conventional Air Spray	: Thin 10 - 20% by volume with White Spirit and adjust to requirement.
	Airless Spray	: Ready for use.
Surface Preparation	Wood	: Wood must be dry and free from grease, dirt and other contaminants. Smoothen the surfaces with suitable grade sandpaper and dust off before application of paints. Surfaces must be dry and free from grease, dirt and other contaminants. Steel surfaces should be sanded or wire-brushed to remove mill scales and rust. For the best result, steel surfaces should be prepared by hand-powered tool according to BS7079 Part 1:1989 ST3 Standard
	Metal	:
Shelf Life	2 years at ambient temperature in unopened containers.	

Paint Guide

Surface Condition	Primer - To Paint 1 Coat	Undercoat - To Paint 1 Coat	Finishing - To Paint 2 Coats
Wood Surfaces	<i>SANcora</i> ® SILVER@Guard	<i>SANcora</i> ® UNDERCOAT@Guard	<i>SANcora</i> ® GLOSS@Guard
Metal Surfaces	<i>SANcora</i> ® RUST@Guard	<i>SANcora</i> ® UNDERCOAT@Guard	<i>SANcora</i> ® GLOSS@Guard

Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.
 In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
 Remove splashes of paint from skin by using soap or water.
 Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
 Ensure good ventilation during application and drying.
 Paint must always be stored in upright position and a cool place.
 Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
 Refer to Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

SANCORA PAINTS INDUSTRIES SDN BHD (19733-T)

Lot 8206, Kawasan Perusahaan Kamunting, 34600 Kamunting, Perak, Malaysia
 Tel: +605-891 8777 (8 Lines) Fax: +605-891 2277 Email: info@sancora.com
 Website: www.sancora.com Facebook: www.facebook.com/SancoraPaint