

TECHNICAL DATA SHEET

TIMBER@Guard

~ Polyurethane Wood Stain ~

Document No: TB-WM-02

SANcora® TIMBER@Guard Polyurethane Wood Stain is specially formulated to enhance the natural beauty of wood and protects it against wood rot and mould growth by its penetrative properties. It is suitable for use on all types of new or previously treated interior hard and soft woods. It gives an extremely durable and flexible finish with excellent abrasion resistance and will not peel, crack or blister.

Usage	Recommended for use on cane or wooden furniture, door paneling, partition and parquet flooring.	
Pack Size	1 litre and 5 litres	
Composition	Pigment	: Lightfast Non-Lead Transparent Pigment
	Binder	: Modified Polyurethane
	Vehicle/Solvent	: Aliphatic & Aromatic Hydrocarbon
Technical Data	Texture	: High Gloss Smooth Finish
	Colour	: Refer to TIMBER@Guard Colourcard
	Theoretical Coverage	: Approx. 16- 18m ² / litre (Depending on surface evenness)
	Drying Time	Single coat at standard thickness (28°C, 50% RH)
		: Touch Dry ≤ 3 hours
		: Hard Dry ≤ 8 hours
	Recoating Time	: 6 hours
	Thinner/Cleaner	: Mineral Spirit
Application	Brush/Roller	: For normal use, thinning is not necessary. If required, add up to 5 - 10% by volume with Mineral Spirit.
	Conventional Air Spray	: Thin 10% by volume with Mineral Spirit and adjust to requirement.
	Airless Spray	: Ready for use.
Surface Preparation	General / New Wood	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish, rubbed down surface in the direction of the grain using suitable abrasive and dust off. If necessary, fill wood grain with appropriate filler and smoothen with abrasive. Allowed paint to dry and lightly dry sand between 1st and 2nd coat.
	Previously Painted Wood	Remove all loose, defective, unstable and existing paint film to bare wood. Rubbed down surface in direction of the grain. If necessary, apply wood grain filler to fill the crack and smoothen with abrasive. Seal the surfaces with <i>SANcora</i> ® TIMBER@Guard Polyurethane Wood Stain .Thin down with 10 - 20% mineral spirit.
Shelf Life	2 years at ambient temperature in unopened containers.	

Paint Guide

Surface Condition	Primer - To Paint 1 Coat	Finishing - To Paint 2 Coats
General / New Wood	<i>SANcora</i> ® TIMBER@Guard Polyurethane Wood Stain Note: thin down with 10 - 20% mineral spirit	<i>SANcora</i> ® TIMBER@Guard Polyurethane Wood Stain
Previously Painted Wood	<i>SANcora</i> ® TIMBER@Guard Polyurethane Wood Stain Note: thin down with 10 - 20% mineral spirit	<i>SANcora</i> ® TIMBER@Guard Polyurethane Wood Stain

Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.
 In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
 Remove splashes of paint from skin by using soap or water.
 Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
 Ensure good ventilation during application and drying.
 Paint must always be stored in upright position and a cool place.
 Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
 Refer to Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

SANCORA PAINTS INDUSTRIES SDN BHD (19733-T)

Lot 8206, Kawasan Perusahaan Kamunting, 34600 Kamunting, Perak, Malaysia

Tel: +605-891 8777 (8 Lines) Fax: +605-891 2277 Email: info@sancora.com

Website: www.sancora.com Facebook: www.facebook.com/SancoraPaint